











A low floor transit bus built on an ARBOC Specialty Vehicles, LLC chassis, the Spirit of Equess easily accommodates up to 33 passengers and six wheelchair passengers. This bus displays true Equal Access for Everyone ® with no steps throughout! ARBOC's advanced technology exceeds ADA guidelines with a 1:8 ramp slope and a 39" entrance door opening for passengers in need of extra assistance and wheelchair accessibility. Backed by a Cummins engine and an Allison transmission, the Spirit of Equess offers superior serviceability and reliability!



For more information contact us at: Phone - 574.825.4880 Fax - 574.825.1750 51165 Greenfield Pkwy, Middlebury, IN 46540 www.ARBOCsv.com

EQUESS by ARBOC

CHASSIS SPECIFICATIONS

- Chassis ARBOC Specialty Vehicles, LLC with GVWR 28,530
- GVWR Front Axle 9,880
- GVWR Rear Axle 18,650
- Engine Cummins ISB 6.7L Diesel/6.7G CNG
- Engine Horse Power 220 @ 2400 RPM
- Top Vehicle Speed 70 MPH
- Torque 520 ft. lbs. @ 1600 RPM
- Estimated Curb Weight 19,250
- Axle Ratio 5.78:1
- Transmission Allison B220 Heavy Duty6-Speed Automatic
- Transmission Shifter Electronic 6 Speed
- Transmission Cooler Rocore 5-7053D
- ZF Front Axle with Air Ride Independent Front Suspension
- ZF Rear Portal Axle with 4 Air Springs
- Air Park Brake Axle Mounted Spring Setting
- Front Kneeling Air Spring Suspension w/ Mechanical Height Control
- WABCO Engine Driven Twin Piston Air Compressor
- VGT Turbo Braking (Diesel Model Only)
- Bendix AD-IS Air Dryer
- Wheels 19.5" x 6.5", 8 Lug
- Tires 245/70R 19.5
- Front Air Brakes/Disc Knorr-Bremse/Bendix Type 14
- Rear Air Brakes/Disc Knorr-Bremse/Bendix 16/24
- Fuel Tank 70 Gal (265 Liters) Diesel or 70 DGE Natural Gas
- Curbside & Roadside Fuel Fills STD
- Radiator Fan Speed Control Type Electric PWM
- Overheat Alarm Temp Setting 225 Degrees
- In-Line Circulation Pumps
- Oil Filter Full Flow/Disposable Type
- Air Cleaner Heavy Duty Cartridge Type
- Front and Rear Mud Flaps
- Steel Front & Rear Bumper Painted Black
- Exhaust Location Streetside Roof
- Daytime Running Lights
- Horn/Dual Note Tone
- Cruise Control
- Rear Tow Hooks

BASE MODELS

- SOE 29' 191" WB
- SOE 34' 254" WB

EXTERIOR BODY & LIGHTS

- Black Rubber Rear Wheel Well Flares
- One Piece Exterior FRP Wall/Skirt
- All Exterior Lights-LED (Incl. Std. Rear Center Mount Brake Light

CONSTRUCTION

- All Tubular Steel Cage Construction
- Bolt & Bonded Construction
- Full Laminated Body
- 5/8" Wood Floor
- Body Width: 100" w/o Mirrors or 121.5" w/ Mirrors
- Body Height: 102" (does not include roof hatch or AC)
- Interior Width 97"/2.46 M
- Interior Height (Front to Rear) 84"/2.13 M
- Entrance Step Height @ Ride Height 13"/330MM
- Entrance Step Height When Kneeling 10"/254MM
- Seating Capacity: Up to 33 Passengers
- Wheel Chair Capacity: up to 6
- Altoona Tested 10 years/350,000 Miles
- Meets All Applicable FMVSS Regulations

ELECTRICAL

- 12-Volt Multiplex Electrical System
- Battery/Group 31 (2) Heavy Duty 1540 CCA Total
- Alternator Leece Neville 320 amp
- Kneel Switch
- Interior Passenger Lights "ON" w/ Door
- Master Battery Disconnect Switch
- Battery Box (Roadside Rear)
- Power Port 12-Volt


INTERIOR

- Driver's Seat USSC G2E (RH Armrest)
- Driver's HVAC
- Left Hand & Right Hand Stanchions Stainless Steel
- Entry Assist Handles Stainless Steel
- Door Header Access Panel

WINDOWS & DOORS

- Solid Framed Windows
- Electric Outward 35" Wide Clear Opening Entrance w/ Handles

29', 191" WB - 23 Passenger



34', 254" WB - 33 Passenger









